L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-GB-0007
DEPTH: 100.5-102.0
S-31

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0001
DEPTH: 1020-1035'
S-32

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-GB-0007
DEPTH: 1035.5'-1050.0'
S.S. 3 3

SOILS TEST CORE BORING NUMBER "CP06-L30PP-CB-0002"

Miami-Dade County, Florida

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG

DIVISION	South Atlantic
INSTALLATION	Jacksonville District
SHEET	1 OF 7 SHEETS
1. PROJECT	L-30 Seepage Management Pilot Project Top Of Levee L-30 (Center of Roadway)
2. BORING DESIGNATION	CP06-L30PP-CB-0002
LOCATION COORDINATES	X = 823,753 Y = 522,044
3. DRILLING AGENCY	Challenge Engineering & Testing, Inc.
CONTRACTOR FILE NO.	2006D30
4. NAME OF DRILLER	Adam Benson
5. DIRECTION OF BORING	☒ VERTICAL ☐ INCLINED
DEG. FROM VERTICAL	
BEARING	
6. THICKNESS OF OVERBURDEN	N/A
7. DEPTH DRILLED INTO ROCK	N/A
8. TOTAL DEPTH OF BORING	109.0 Ft.
9. SIZE AND TYPE OF BIT	See Remarks
10. COORDINATE SYSTEM/DATUM	State Plane, FLE (U.S. Ft.)
HORIZONTAL	NAD83
VERTICAL	NAVD88
11. MANUFACTURER'S DESIGNATION OF DRILL	CME 55 Truckrig
☐ AUTO HAMMER ☒ MANUAL HAMMER	
12. TOTAL SAMPLES	DISTURBED 33 / UNDISTURBED (UD) 0
13. TOTAL NUMBER CORE BOXES	4
14. ELEVATION GROUND WATER	5.0 Ft.
15. DATE BORING	STARTED 10-06-06 / COMPLETED 10-17-06
16. ELEVATION TOP OF BORING	17.5 Ft.
17. TOTAL RECOVERY FOR BORING	65 %
18. SIGNATURE AND TITLE OF INSPECTOR	Bob Momberger, Geologist

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/0.5 FT.	N-VALUE
17.5	0.0						17.5		
			L-30 Levee Fill Material						
							Advanced Boring w/ tricone roller bit		

0 5 10 15

SAJ FORM 1836
JUN 02

(Continued)

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 2 OF 7 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 823,753 Y = 522,044	17.5 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
							Advanced Boring w/ tricone roller bit		
0.2	17.3						0.2		
			LIMESTONE, oolitic, sparsely fossiliferous, soft, moderately weathered, fine-grained, thin bedding, vuggy, Ft. Thompson Formation, 2.5Y 8/2 pale yellow	81	1	RQD 20	4 x 5-1/2" Diamond Impregnated Bit DT = 1 mins HP = 250 psi DFR = 50 %		
-2.5	20.0						-2.5		
			LIMESTONE, hard, moderately weathered, fine-grained, thick bedding, pitted, 5Y 8/1 white	100	2	RQD 85	4 x 5-1/2" Diamond Impregnated Bit DT = 4 mins HP = 250 psi DFR = 25 %		
			At El. -4.0 Ft., 5Y 7/3 pale yellow		BOX 1				
-5.5	23.0		LIMESTONE, fossiliferous, moderately hard, slightly weathered, aphanitic, thick bedding, vuggy, 5Y 8/2 pale yellow				-7.5		
			At El. -9.5 Ft., thin bedding, 5Y 8/1 white	60	3	RQD 10	4 x 5-1/2" Diamond Impregnated Bit DT = 3 mins HP = 250 psi DFR = 0 %		
-12.5	30.0						-12.5		
			SAND, silty, soft, mostly subangular fine-grained sand-sized carbonate, strong reaction with HCl, wet, 2.5Y 8/2 pale yellow (SM)						
-14.5	32.0								
			LIMESTONE, fossiliferous, moderately hard, moderately weathered, fine-grained, thin bedding, vuggy, 5Y 8/1 white	60	BOX 2	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 4 mins HP = 250 psi DFR = 0 %		
			At El. -17.0 Ft., 5Y 6/4 pale olive						
							-17.5		

Moderately Weathered

Slightly Weathered

Moderately Weathered

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 3 OF 7 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 823,753 Y = 522,044	17.5 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
	Moderately Weathered		From El. -20.5 to -31.5 Ft., unweathered, aphanitic, thin bedding, pitted, 5Y 8/1 white	60	5	RQD 25	4 x 5-1/2" Diamond Impregnated Bit DT = 3 mins HP = 250 psi DFR = 0 %		
							-22.5		
				60	BOX 2	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 5 mins HP = 250 psi DFR = 0 %		
							-27.5		
	Unweathered		From El. -31.5 to -37.5 Ft., soft, unweathered, aphanitic, thin bedding, pitted, clay filled pits	66	7	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 5 mins HP = 250 psi DFR = 0 %		
							-32.5		
	Unweathered			60	BOX 3	RQD 25	4 x 5-1/2" Diamond Impregnated Bit DT = 6 mins HP = 250 psi DFR = 0 %		
							-37.5		

35 40 45 50 55

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 4 OF 7 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 823,753 Y = 522,044	17.5 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
		Mod. Weathered	From El. -37.5 to -39.5 Ft., moderately hard, moderately weathered, aphanitic, thin bedding, vuggy, 5Y 7/2 light gray						
		Unweathered	From El. -39.5 to -43.5 Ft., soft, unweathered, aphanitic, thin bedding, pitted, clay filled pits, 5Y 8/1 white	25	9	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 4 mins HP = 250 psi DFR = 0 %		
							-42.5		
		Mod. Weathered	From El. -43.5 to -46.0 Ft., moderately hard, moderately weathered, aphanitic, thin bedding, vuggy, sand filled vugs, 5Y 7/3 pale yellow	20	BOX 10 3	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 6 mins HP = 250 psi DFR = 0 %		
							-47.5		
		Unweathered	From El. -46.0 to -51.5 Ft., moderately weathered, aphanitic, thin bedding, pitted, clay filled pits, 10YR 7/2 light gray	80	11	RQD 8	4 x 5-1/2" Diamond Impregnated Bit DT = 6 mins HP = 250 psi DFR = 0 %		
							-52.5		
		Unweathered	From El. -51.5 to -55.5 Ft., unweathered, aphanitic, medium bedding, vuggy, sand filled vugs, 10YR 8/2 very pale brown	90	BOX 12 4	RQD 60	4 x 5-1/2" Diamond Impregnated Bit DT = 3 mins HP = 250 psi DFR = 0 %		
							-57.5		
-57.5	75.0	Mod. Weathered	From El. -55.5 to -57.5 Ft., moderately weathered, fine-grained, thick bedding, pitted, sand filled pits, 2.5Y 6/1 gray						

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 5 OF 7 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 823,753 Y = 522,044	17.5 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/0.5 FT.	N-VALUE
-61.5	79.0	Slightly Weathered	LIMESTONE, soft, slightly weathered, aphanitic, 5Y 7/3 pale yellow	0	BOX 13 4	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 2 mins HP = 250 psi DFR = 0 % -61.5		
-62.5	80.0	Wea.	LIMESTONE, fossiliferous, soft, slightly weathered, aphanitic, pitted, sand filled pits, 5Y 7/3 pale yellow	20	14		SPT Sampler	WOR 0 0	0
			SHELL, mostly angular coarse-grained sand-sized shell up to 1/2", little clay, strong reaction with HCl, wet, Pinecrest Sand Formation, 2.5Y 7/1 light gray				-63.0		
				40	15		SPT Sampler	7 12 11	23
			At El. -64.5 Ft., some coarse gravel-sized limestone up to 1"				-64.5		
				97	16		SPT Sampler	7 14 14	28
							-66.0		
				73	17		SPT Sampler	8 17 16	33
							-67.5		
-68.5	86.0			100	18		SPT Sampler	7 8 8	16
			SAND, clayey, nonplastic, soft, mostly fine-grained sand-sized carbonate, little clay, strong reaction with HCl, wet, 2.5Y 7/1 light gray (SC)				-69.0		
-70.0	87.5			50	19		SPT Sampler	12 14 15	29
			SHELL, mostly angular coarse-grained sand-sized shell up to 1/4", some coarse-grained sand-sized limestone up to 1/2", little clay, strong reaction with HCl, wet, 2.5Y 6/1 gray				-70.5		
				77	20		SPT Sampler	12 12 14	26
							-72.0		
				90	21		SPT Sampler	14 8 10	18
							-73.5		
-74.5	92.0		At El. -73.5 Ft., nonplastic, mostly angular medium-grained sand-sized shell up to 1/4", little fine to medium-grained sand-sized carbonate, strong reaction with HCl, wet, 2.5Y 6/1 gray	90	22		SPT Sampler	10 8 7	15
							-75.0		
			CLAY, lean, medium plasticity, soft, mostly clay, some shell up to 1/4", little fine-grained sand-sized carbonate, strong reaction with HCl, wet, 2.5Y 5/1 gray (CL)	90	23		SPT Sampler	5 7 7	14
							-76.5		
			At El. -76.5 Ft., some fine-grained sand-sized quartz, little coarse-grained sand-sized shell, strong reaction with HCl,	90	24		SPT Sampler	6 5	

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 6 OF 7 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 823,753 Y = 522,044	17.5 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
			wet, 10Y 6/1 greenish gray	90	24		-78.0 SPT Sampler	5	10
-78.5	96.0							15	
			SAND, silty, very soft, mostly fine-grained sand-sized quartz, little silt, little coarse-grained sand-sized shell up to 1/4", strong reaction with HCl, wet, 10Y 7/1 light greenish gray (SM)	67	25		SPT Sampler	15	23
							-79.5	8	
				47	26		SPT Sampler	7	
								14	28
-81.0	98.5						-81.0	14	
			SHELL, mostly angular fine to coarse gravel-sized shell up to 3/4", little fine-grained sand-sized quartz, little sand to gravel-sized limestone up to 1/2", few silt, strong reaction with HCl, wet, 10Y 7/1 light greenish gray	90	27		SPT Sampler	7	
			At El. -82.5 Ft., few fine-grained sand-sized quartz					14	35
							-82.5	21	
				90	28		SPT Sampler	22	
								23	44
							-84.0	21	
			At El. -85.0 Ft., some fine to medium-grained sand-sized quartz, trace sand to gravel-sized shell up to 3/4"	90	29		SPT Sampler	12	
								11	20
							-85.5	9	
				90	30		SPT Sampler	5	
								10	20
-87.5	105.0						-87.0	10	
			SAND, silty, some fine-grained sand-sized quartz, little fine-grained sand-sized carbonate, little sand to gravel-sized shell up to 1/2", strong reaction with HCl, wet, 10Y 6/1 greenish gray (SM)	90	31		SPT Sampler	17	
			At El. -88.5 Ft., few coarse-grained sand-sized limestone up to 1/4"					23	65
							-88.5	42	
				90	32		SPT Sampler	27	
								37	74
							-90.0	37	
				97	33		SPT Sampler	14	
								34	71
-91.4	108.9						-91.5	37	
			LIMESTONE, fossiliferous, moderately hard, coarse-grained, pitted, clay filled pits, 10Y 6/1 greenish gray				140# hammer w/30" drop used with 2.0' split spoon (1-3/8" I.D. x 2" O.D.).		

NOTES:

1. Soils are field visually classified in accordance with the Unified Soils Classification System.

2. Set 17.5 Ft. of 8" Schedule 40 PVC Pipe Through Center of L-30 Levee To Top of Rock.

3. Boring Drilled/Sampled In Three Phases:
A. Set Surface Casing.
B. 4" Wireline Rock Coring To Base Of Rock.
C. Splitspoon Sampling 30 Ft. Below Base of Rock.

Abbreviations:
WOR = Weight of Rods.
DT = Drill Time.
HP = Hydraulic Pressure.
DFR = Drill Fluid Return.

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0002

DRILLING LOG (Cont. Sheet)	INSTALLATION		SHEET 7 OF 7 SHEETS
	Jacksonville District		
PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88
LOCATION COORDINATES	ELEVATION TOP OF BORING		
X = 823,753 Y = 522,044	17.5 Ft.		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
			4. Borehole Reamed To 7.5" To Base of Rock. USGS Performed Borehole Logging. 5. 2" Monitoring Well Set @ X = 823754 Y= 522036 Screen From -40.7 to -42.7 Ft. 6. Cored to 80 Ft. To Confirm Out of Rock 7. Boring sealed with available sediment.						

115
120
125
130
135

SAJ FORM 1836-A
JUN 02

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 17.3-20.0
S. Run #1

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 200-250'
S-Run #2

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 25.0-30.0'
S. Run #3

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 30.0-35.0'
S- Run # 4

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 350-400
S. Run #5

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 40.0-45.0'
S- Run#6

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 45.0-50.0'
S- RUN#7

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 50.0-55.0'
S. Run # 8

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 55.0-60.0
S. Run #9


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 60.0-65.0
S- Run #10

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 65-70'
S- Run # 11

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 700-750'
S. RUN #12

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-GB-0002
DEPTH: 79.0-80.5'
S: 14
60
BAGS


L30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-GB-0002
DEPTH: 80.5-82.0
S.I. 15

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-0002
DEPTH: 82.0-83.5'
S-16
60
BAGS


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 83.5-85.0'
S-17

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-GB-0002
DEPTH: 85.0-86.5'
S-18

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-0002
DEPTH: 86.5-88.0'
S-19


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 88.0-89.5
S-20

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 8.5-9.0'
S-21
60
BAGS


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 91.0-92.5'
S- 22


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 92.5-94.0'
S-23

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 94.0-95.5'
S. 94
SKY
60
BAGS

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-000 2
DEPTH: 95.5-97.0
S: 25


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 97.0-98.5'
S- 26

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-0002
DEPTH: 98.5-100.0'
S.

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 101.5-103.0'
S. 38

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0002
DEPTH: 101.5-103.0'
S-
60
BAGS

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-0002
DEPTH: 1030-1045'
S: 30
USKY
STRING
60
BAGS

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-0002
DEPTH: 104.5-106.0'
S-31
USKY
60
BAGS

L-30 SEEPAGE MGMT PILOT PGT
GP06-L30PP-CB-0002
DEPTH: 1060-1075
S: 3
USKY
60
BAGS


L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0000 2
DEPTH: 107.5-109.0'
S-33

SOILS TEST CORE BORING NUMBER "CP06-L30PP-CB-0003"

Miami-Dade County, Florida

Boring Designation CP06-L30PP-CB-0003

DRILLING LOG

DIVISION: South Atlantic	INSTALLATION: Jacksonville District	SHEET 1 OF 6 SHEETS	
1. PROJECT: L-30 Seepage Management Pilot Project; Top Of Levee L-30 (Center of Roadway)	9. SIZE AND TYPE OF BIT: See Remarks		
	10. COORDINATE SYSTEM/DATUM: State Plane, FLE (U.S. Ft.)	HORIZONTAL: NAD83	VERTICAL: NAVD88
2. BORING DESIGNATION: CP06-L30PP-CB-0003	LOCATION COORDINATES: X = 821,358 Y = 519,743	11. MANUFACTURER'S DESIGNATION OF DRILL: CME 55 Truckrig	☐ AUTO HAMMER ☒ MANUAL HAMMER
3. DRILLING AGENCY: Challenge Engineering & Testing, Inc.	CONTRACTOR FILE NO.: 2006D30	12. TOTAL SAMPLES	DISTURBED: 33 / UNDISTURBED (UD): 0
4. NAME OF DRILLER: Adam Benson		13. TOTAL NUMBER CORE BOXES: 5	
5. DIRECTION OF BORING: ☒ VERTICAL ☐ INCLINED	DEG. FROM VERTICAL:	BEARING:	14. ELEVATION GROUND WATER: 5.0 Ft.
		15. DATE BORING	STARTED: 10-07-06 / COMPLETED: 10-18-06
6. THICKNESS OF OVERBURDEN: N/A		16. ELEVATION TOP OF BORING: 17.2 Ft.	
7. DEPTH DRILLED INTO ROCK: N/A		17. TOTAL RECOVERY FOR BORING: 73 %	
8. TOTAL DEPTH OF BORING: 105.0 Ft.		18. SIGNATURE AND TITLE OF INSPECTOR: Bob Momberger, Geologist	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	ROD OR UD	REMARKS	BLOWS/0.5 FT.	N-VALUE
17.2	0.0						17.2		
			L-30 Levee Fill Material						
							Advanced Boring w/ tricone roller bit		

0 5 10 15

SAJ FORM 1836
JUN 02

(Continued)

Boring Designation CP06-L30PP-CB-0003

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 2 OF 6 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 821,358 Y = 519,743	17.2 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
							Advanced Boring w/ tricone roller bit		
-0.3	17.5						-0.3		
			LIMESTONE, oolitic, sparsely fossiliferous, moderately hard, slightly weathered, fine-grained, thick bedding, vuggy, peat filled vugs, Ft. Thompson Formation, 2.5Y 8/2 pale yellow	100	1	RQD 50	4 x 5-1/2" Diamond Impregnated Bit DT = 3 mins HP = 250 psi DFR = 50 %		
			At El. -2.8 Ft., vuggy, quartz filled vugs				-2.8		
			From El. -4.3 to -12.8 Ft., aphanitic, thick bedding, pitted, sand filled pits, 2.5Y 7/2 light gray	100	2 BOX 1	RQD 30	4 x 5-1/2" Diamond Impregnated Bit DT = 6 mins HP = 250 psi DFR = 25 %		
			At El. -6.8 Ft., pitted, clay filled pits				-7.8		
				70	3	RQD 45	4 x 5-1/2" Diamond Impregnated Bit DT = 5 mins HP = 250 psi DFR = 0 %		
-12.8	30.0						-12.8		
			LIMESTONE, fossiliferous, very soft, slightly weathered, aphanitic, thin bedding, vuggy, clay filled vugs, 2.5Y 8/1 white	6	BOX 2 4	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 3 mins HP = 250 psi DFR = 0 %		
							-17.8		

Slightly Weathered

15 20 25 30 35

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0003

DRILLING LOG (Cont. Sheet)	INSTALLATION: Jacksonville District	SHEET 3 OF 6 SHEETS
PROJECT: L-30 Seepage Management Pilot Project	COORDINATE SYSTEM/DATUM: State Plane, FLE (U.S. Ft.)	HORIZONTAL: NAD83 / VERTICAL: NAVD88
LOCATION COORDINATES: X = 821,358 Y = 519,743	ELEVATION TOP OF BORING: 17.2 Ft.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/0.5 FT.	N-VALUE
			At El. -17.8 Ft., sparsely fossiliferous, moderately hard, slightly weathered, aphanitic, thick bedding, pitted	90	5	RQD 50	4 x 5-1/2" Diamond Impregnated Bit DT = 4 mins HP = 250 psi DFR = 0 %		
			At El. -21.8 Ft., fossiliferous				-22.8		
			At El. -25.8 Ft., soft, vuggy, clay filled vugs	96	BOX 2 6	RQD 20	4 x 5-1/2" Diamond Impregnated Bit DT = 2 mins HP = 250 psi DFR = 0 %		
			At El. -27.3 Ft., moderately hard, unweathered, aphanitic, medium bedding, vuggy, sand filled vugs, 5Y 8/1 white				-27.8		
				70	7	RQD 20	4 x 5-1/2" Diamond Impregnated Bit DT = 3 mins HP = 250 psi DFR = 0 %		
							-32.8		
				90	BOX 3 8	RQD 25	4 x 5-1/2" Diamond Impregnated Bit DT = 4 mins HP = 250 psi DFR = 0 %		
							-37.8		

Unweathered

35 40 45 50 55

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0003

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 4 OF 6 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 821,358 Y = 519,743	17.2 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
		Slightly Weathered	At El. -37.8 Ft., slightly weathered, pitted, 2.5Y 8/1 white	70	9 BOX 3	RQD 20	4 x 5-1/2" Diamond Impregnated Bit DT = 2 mins HP = 250 psi DFR = 0 %		
							-42.8		
-44.8	62.0	Unweathered	LIMESTONE, hard, unweathered, pitted, 2.5Y 6/1 gray	80	10	RQD 20	4 x 5-1/2" Diamond Impregnated Bit DT = 7 mins HP = 250 psi DFR = 0 %		
							-47.8		
			At El. -47.8 Ft., moderately weathered, thin bedding, vuggy, clay filled vugs						
-49.8	67.0	Moderately Weathered	LIMESTONE, soft, clay filled vugs	40	11 BOX 4	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 2 mins HP = 250 psi DFR = 0 %		
							-52.8		
-54.8	72.0		SHELL, mostly angular sand to gravel-sized shell up to 1/2", few fine-grained sand-sized carbonate, trace limestone up to 1/8", strong reaction with HCl, wet, 5Y 7/1 light gray	20	12	RQD 0	4 x 5-1/2" Diamond Impregnated Bit DT = 1 mins HP = 250 psi DFR = 0 %		
			At El. -57.1 Ft., little fine-grained sand-sized carbonate, Pinecrest Sand Formation				-57.8		

55 60 65 70 75

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0003

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 5 OF 6 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 821,358 Y = 519,743	17.2 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/ 0.5 FT.	N-VALUE
				0	13	RQD 0	4 x 5-1/2" Diamond Impregnated Bit		
				67	14		SPT Sampler	4 2 2	4
							-59.3		
				73	15		SPT Sampler	3 2 4	6
							-60.8		
				73	16		SPT Sampler	3 2 3	5
			At El. -62.3 Ft., mostly angular fine to coarse gravel-sized shell up to 1/2", few silt, few clay, strong reaction with HCl, wet, 10Y 6/1 greenish gray				-62.3		
				47	17		SPT Sampler	7 6 6	12
							-63.8		
				97	18		SPT Sampler	5 4 7	11
-65.3	82.5						-65.3		
			SAND, silty, mostly fine-grained sand-sized carbonate, little angular sand to gravel-sized shell up to 1/2", few sandstone, strong reaction with HCl, wet, moderate cementation, N 6/ gray (SM)	100	19		-65.6 SPT Sampler	50/0.3'	
-66.8	84.0						Advanced Boring -66.8		
			SHELL, low plasticity, mostly angular sand to gravel-sized shell up to 1/2", little clay, few silt, strong reaction with HCl, wet, 10Y 6/1 greenish gray	90	20		SPT Sampler	14 14 17	31
							-68.3		
				53	21		SPT Sampler	9 19 21	40
							-69.8		
			At El. -69.8 Ft., mostly angular fine gravel-sized shell up to 3/4", few silt, strong reaction with HCl, wet, 10Y 6/1 greenish gray	80	22		SPT Sampler	19 22 26	48
			At El. -71.3 Ft., little silt				-71.3		
				90	23		SPT Sampler	22 21 17	38
-72.8	90.0						-72.8		
			SAND, silty, mostly medium-grained sand-sized quartz, some angular medium-grained sand-sized shell up to 1/4", strong reaction with HCl, wet, N 6/ gray (SM)	97	24		SPT Sampler	11 12 15	27
							-74.3		
				97	25		SPT Sampler	14 14 14	28
							-75.8		
				97	26		SPT Sampler	9 6 7	13
							-77.3		
				67	27		SPT Sampler	8	

SAJ FORM 1836-A
JUN 02

Boring Designation CP06-L30PP-CB-0003

DRILLING LOG (Cont. Sheet)	INSTALLATION	SHEET 6 OF 6 SHEETS
	Jacksonville District	

PROJECT	COORDINATE SYSTEM/DATUM	HORIZONTAL	VERTICAL
L-30 Seepage Management Pilot Project	State Plane, FLE (U.S. Ft.)	NAD83	NAVD88

LOCATION COORDINATES	ELEVATION TOP OF BORING
X = 821,358 Y = 519,743	17.2 Ft.

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR CD	REMARKS	BLOWS/0.5 FT.	N-VALUE
			At El. -77.8 Ft., some angular sand to gravel-sized shell up to 1/2", trace silt, strong reaction with HCl, wet, N 6/ gray	67	27		SPT Sampler	5 6	11
			At El. -78.8 Ft., some angular sand to gravel-sized shell up to 1"	97	28		SPT Sampler -78.8	2 3 7	10
				97	29		SPT Sampler -80.3	29 25 23	48
			At El. -81.8 Ft., little angular medium-grained sand-sized shell up to 1/4", strong reaction with HCl, wet, N 6/ gray	97	30		SPT Sampler -81.8	12 20 27	47
			At El. -83.3 Ft., some angular sand to gravel-sized shell up to 1"	93	31		SPT Sampler -83.3	10 26 28	54
			At El. -84.8 Ft., some angular sand to gravel-sized shell up to 1-1/2"	70	32		SPT Sampler -84.8	15 26 13	39
			At El. -86.3 Ft., little angular sand to gravel-sized shell up to 1/2", weak cementation, 10Y 7/1 light greenish gray	73	33		SPT Sampler -86.3	6 7 8	15
-87.8	105.0						-87.8		

NOTES:

1. Soils are field visually classified in accordance with the Unified Soils Classification System.

2. Set 17.5 Ft. of 8" Schedule 40 PVC Pipe Through Center of L-30 Levee To Top of Rock.

3. Boring Drilled/Sampled In Three Phases:
A. Set Surface Casing.
B. 4" Wireline Rock Coring To Base Of Rock.
C. Splitspoon Sampling 30 Ft. Below Base of Rock.

4. Borehole Reamed To 7.5" To Base of Rock. USGS Performed Borehole Logging.

5. 2" Monitoring Well Set @
X = 821356 Y= 519734

Screen From -41.8 to -43.8 Ft.

6. Cored to 80 Ft. To Confirm Out of Rock

7. Boring sealed with available sediment.

140# hammer w/30" drop used with 2.0' split spoon (1-3/8" I.D. x 2" O.D.).

Abbreviations:
DT = Drill Time.
HP = Hydraulic Pressure.
DFR = Drill Fluid Return.

95
100
105
110
115

SAJ FORM 1836-A
JUN 02

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 175-200'
S. Run#1

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 200-250'
S. Run #2

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 25.0 - 30.0
S. RUN #3

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 30.0-35.0
S- Run#4

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 35.0-40.0'
S. RUN #5

L-30 SEEPAGE MGMT PILOT PROJ
CP06-L30PP-CB-0003
DEPTH: 40.0-45.0'
S. Run#6

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-000 3
DEPTH: 450-500
S. Run#7

L-30 SEEPAGE MGMT PILOT PGT
CP06-L30PP-CB-0003
DEPTH: 50.0-55.0'
S. Run #8